

Printing date 03.02.2015 Version number 1 Revision: 03.02.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: <u>Liquid Power</u>Article number: PK.10.16

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

• Sector of Use SU21 Consumer uses: Private households / general public / consumers

SU3 Industrial uses: Uses of substances as such or in preparations at industrial

sites

SU22 Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

Process category
 PROC7 Industrial spraying

PROC11 Non industrial spraying

· Application of the substance /

the mixture Auxiliary

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Putoline Oil

Dollegoorweg 15 NL-7602 EC ALMELO Tel.: +31 (0)546 818165

· Further information obtainable

from: Product safety department - vib@putoline.com

· 1.4 Emergency telephone

number: +31 (0)546 818165 (9 AM to 4 PM, Monday to Friday)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.



Xi; Irritant

R38: Irritating to skin.

) F; H

F; Highly flammable

R11: Highly flammable.



N; Dangerous for the environment

Printing date 03.02.2015 Version number 1 Revision: 03.02.2015

Trade name: Liquid Power

(Contd. of page 1)

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

 Information concerning particular hazards for human

and environment: The product has to be labelled due to the calculation procedure of the "General

Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotising effect.

· Classification system: The classification is according to the latest editions of the EU-lists, and extended by

company and literature data.

· 2.2 Label elements

· Hazard pictograms

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

GHS02







· Signal word Danger

· Hazard-determining

components of labelling: hydrocarbons, c7, n-alkanes, isoalkanes, cyclics

Distillates (petroleum), hydrotreated heavy paraffinic

• **Hazard statements** H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

• Precautionary statements P101 If medical advice is needed, have product container or label at

hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

P271 Use only outdoors or in a well-ventilated area. P301+P310 IF SWALLOWED: Immediately call a doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/

national/international regulations.

· 2.3 Other hazards

 \cdot Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Solvent mixture with additives

· Dangerous components:		
EC number: 927-510-4	hydrocarbons, c7, n-alkanes, isoalkanes, cyclics	50-100%
Reg.nr.: 01-2119475515-33	🗶 Xn R65; 🗶 Xi R38; 🔥 F R11; 🝢 N R51/53	
	R67	
	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	25-50%
EINECS: 265-157-1	X Xn R65	
Reg.nr.: 01-2119484627-25	♦ Asp. Tox. 1, H304	
CAS: 12001-85-3	zinc naphthenate	0.1-1.0%
EINECS: 234-409-2	₩ N R51/53	
	Aquatic Chronic 2, H411	

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date 03.02.2015 Version number 1 Revision: 03.02.2015

Trade name: Liquid Power

(Contd. of page 2)

After eye contact:
 After swallowing:
 Rinse opened eye for several minutes under running water.
 Do not induce vomiting; call for medical help immediately.

 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special

treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, dry chemical, or foam. Water can be used to cool and protect exposed

material.

· For safety reasons unsuitable

extinguishing agents:

• 5.2 Special hazards arising

Water with full jet

from the substance or mixture

• 5.3 Advice for firefighters

Formation of toxic gases is possible during heating or in case of fire.

· Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Wear fully protective suit.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents Remove from the water surface (e.g. skim or suck off).

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store in a cool location.

· Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about

design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 03.02.2015 Revision: 03.02.2015 Version number 1

Trade name: Liquid Power

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNEL (Derived No Effect Level) for workers:				
hydrocarbons, c7, n-alkanes, isoalkanes, cyclics				
Dermal	Long-term - systemic effects, worker	300 mg/kg bw/day (worker)		
Inhalative	Long-term - systemic effects, worker	2085 mg/m³ (worker)		

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and

hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection: Filter A

In case of brief exposure or low pollution use respiratory filter device. In case of

intensive or longer exposure use self-contained respiratory protective device. · Protection of hands:

Wear gloves for the protection against chemicals according to EN 374.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Solvent resistant gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also

> on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is

dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles (EN 166)

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Colour: Blue

· Odour: Characteristic · Odour threshold: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 83 °C

· Flash point: -5 °C

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 5)

Printing date 03.02.2015 Version number 1 Revision: 03.02.2015

Trade name: Liquid Power

(Contd. of page 4)

· **Self-igniting:** Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 8 Vol %

 Density at 20 °C:
 0.795 g/cm³

Density at 20 °C:
 Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Solvent content:

Organic solvents: 60.7 %

Solids content: 0.3 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· 10.3 Possibility of hazardous

reactions
10.4 Conditions to avoid
10.5 Incompatible materials:

Reacts with strong oxidising agents.
No further relevant information available.
No further relevant information available.

· 10.6 Hazardous decomposition

products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· Primary irritant effect:

· on the skin: Irritant to skin and mucous membranes.

• on the eye: No irritating effect.

Sensitisation: No sensitising effects known.

· Additional toxicological

information: The product shows the following dangers according to the calculation method of the

General EU Classification Guidelines for Preparations as issued in the latest

version: Irritant

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

hydrocarbons, c7, n-alkanes, isoalkanes, cyclics

LL/EL/IL50 >13.4 mg/l (fish)

· 12.2 Persistence and

degradability
 Other information:
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.
 No further relevant information available.

· Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

• **General notes:** Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

• 12.5 Results of PBT and vPvB assessment • PBT: Not applicable.

vPvB: Not applicable.12.6 Other adverse effects No further relevant information available.

(Contd. on page 6)

Printing date 03.02.2015 Version number 1 Revision: 03.02.2015

Trade name: Liquid Power

(Contd. of page 5)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
20 01 99	other fractions not otherwise specified	
07 01 04*	* other organic solvents, washing liquids and mother liquors	
15 01 04	metallic packaging	

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations

· Recommendation:	Disposal must be made according to official regulations.
SECTION 14: Transport info	ormation
· 14.1 UN-Number · ADR,ADN, IMDG, IATA	UN1993
· 14.2 UN proper shipping name · ADR/ADN	1993 FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50 °C not more than 110 kPa) (hydrocarbons, c7, n-alkanes, isoalkanes, cyclics), ENVIRONMENTALLY HAZARDOUS
· IMDG	FLAMMABLE LIQUID, N.O.S. (hydrocarbons, c7, n-alkanes, isoalkanes, cyclics, zinc naphthenate), MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (hydrocarbons, c7, n-alkanes,
	isoalkanes, cyclics)
· 14.3 Transport hazard class(es	5)
· ADR,ADN, IMDG	
· Class · Label	3 Flammable liquids.
·IATA	
Class Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR,ADN, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: hydrocarbons, c7, n-alkanes, isoalkanes, cyclics
Marine pollutant: Special marking (ADR/ADN):	Yes Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for us Danger code (Kemler): EMS Number:	
· 14.7 Transport in bulk according MARPOL73/78 and the IBC Co.	
· Transport/Additional informati	
· ADR/ADN · Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E

Printing date 03.02.2015 Revision: 03.02.2015 Version number 1

Trade name: Liquid Power

(Contd. of page 6)

IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50 °C not more than 110 kPa) (hydrocarbons, c7, n-alkanes, isoalkanes, cyclics), ENVIRONMENTALLY HAZARDOUS, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations:

· VOC-EU 607.0 g/l

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

May cause drowsiness or dizziness. H336

H411 Toxic to aquatic life with long lasting effects.

Highly flammable. Irritating to skin. R38

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Harmful: may cause lung damage if swallowed. R65 R67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Product safety department. · Contact: Product safety department

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer · Abbreviations and acronyms:

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· Sources 67/548/EEC

99/45/EEC EC/453-2010