

SHINKO TIRES / PNEUS SHINKO

SHINKO
MOTORCYCLE TIRES

CODE B | KEYWORD 9

Front / Avant

Front/Rear
Avant/Arrière

SR714/704

- Tough Nylon carcass
- 4 Ply rated DOT approved
- Moped Fitment
- L speed rating (75mph), Tube Type. P Speed rating (93 mph)

SPEED RATING / INDICE DE VITESSE

Code	MPH	KM/H
L	75	120
P	94	150

DOT



Part No.	Size	Load Index	Speed Rating	Diameter	Width	DOT	Ply Rating	Tube Type	Max Load
Front									
01-04116	80/80-16 SR714	45	P	21.02	3.15	Y	4	TL	364
01-04117	90/80-16 SR714	51	P	21.65	3.54	Y	4	TL	430
Front/Rear									
01-04195	2.25-16 SR714	31	L	20.87	2.32	Y	4	TT	240
01-04196	2.25-17 SR704	33	L	21.89	2.32	Y	4	TT	254

504/505 SERIES "MOBBER"

SÉRIE 504/505 "MOBBER"

Designed to work in hard terrain, the 504 and 505 offers exceptional traction, braking, stability, and control.

- Featuring high carbon compound tread designs
- Maximizing tread wear and minimize tread knob tear/wear
- Offering great traction, braking and overall stability for enhanced control
- Reinforced knobs resist tearing and chunking while providing consistent grip
- 504/505 Mobber versions (01-04339 & 01-04340) are DOT Approved

SPEED RATING / INDICE DE VITESSE

Code	MPH	KM/H
P	94	150

DOT

Front / Avant

Rear / Arrière



Part No.	Size	Load Index	Speed Symbol	Rim Size	Diameter	Width	Ply Rating	Tube Type	Max Load	Max PSI
Front										
01-04339	120/70-12 Mobber	51	P	3.5	18.62	4.8	4	T/L	195	33
Rear										
01-04340	130/70-12 Mobber	56	P	3.5	19.17	5.08	4	T/L	224	33

520 SERIES (INTERMEDIATE/HARD)

SÉRIE 520 (INTERMÉDIAIRE/DUR)

- For intermediate to hard terrain
- Tread pattern works well in a wide variety of soil conditions
- Reinforced knobs resist tearing and chunking

See Page 784 for Terrain Guide

Voir la page 784 pour le guide du terrain

SPEED RATING / INDICE DE VITESSE

Code	MPH	KM/H
J	62	100
M	81	130

DOT

Front / Avant

Rear / Arrière



Part No.	Size	Load Index	Speed Symbol	Rim Size	Diameter	Width	Ply Rating	Tube Type	Max Load	Maximum Air Pressure (PSI)
Front										
01-04123	2.50-10	33	J	1.5	15.31	2.56	4	T/T	115	36
01-04143	80/100-21	51	M	1.85	27.28	3.15	4	T/T	195	33
Front/Rear										
01-04197	2.50-12	33	J	1.5	17.32	2.56	4	T/T	115	36
Rear										
01-04124	2.75-10	38	J	1.85	15.71	2.83	4	T/T	132	36
01-04183	90/100-14	49	M	2.15	21.1	3.54	4	T/T	185	33
01-04151	110/100-18	64	M	2.5	26.73	4.29	4	T/T	280	33
01-04150	110/90-19	68	M	2.75	27.44	4.69	4	T/T	315	33

