

## SHINKO TIRES / PNEUS SHINKO

**SHINKO**  
MOTORCYCLE TIRES

CODE B | KEYWORD 9

**505 HYBRID CHEATER (HARD ENDURO/EXTREME SINGLE TRACK)**  
**505 HYBRID CHEATER (ENDURO DIFFICILE/PISTE EXTRÊME SIMPLE)**

New Hybrid Hard Enduro / Extreme single track trail tire finds traction in the most extreme conditions—it's almost like cheating!

- The Cheater Hybrids a soft sticky trials style rubber compound on a moto-style carcass
- Tread design and unique rubber compound works well in a wide variety of soil conditions
- Where a Trials tire falls short in braking and lose soil conditions, the 505 "Cheater" bridges that gap to make it the Ultimate Hybrid off-road tire
- The 505 Cheater shines in dry, harder conditions
- Adds confidence even in the most demanding terrain
- Available in popular 18" and 19" sizes
- NHS (Not for Highway Service)

## SPEED RATING / INDICE DE VITESSE

Code	MPH	KM/H
M	81	130

Part No.	Size	Load Index	Speed Symbol	Rim Size	Diameter	Width	Ply Rating	Tube Type	Max Load	Maximum Air Pressure (PSI)
<b>Rear</b>										
01-04271	110/100-18	64	M	2.5	26.65	4.29	4	T/T	280	33
01-04272	120/100-18	68	M	2.75	27.44	4.69	4	T/T	315	33
01-04273	110/90-19	62	M	2.5	26.81	4.29	4	T/T	265	33
01-04274	120/90-19	66	M	2.75	27.48	4.69	4	T/T	299	33

**525 HYBRID "CHEATER"**  
**(SOFT/INTERMEDIATE TERRAIN)**  
**(TERRAIN SOUPLE/INTERMÉDIAIRE)**

Hybrid Cheater intermediate terrain Enduro/Extreme single track trail tire finds traction in the most extreme conditions.

- The Cheater Hybrids a soft sticky trials style rubber compound on a moto-style carcass
- Tread design and unique rubber compound works well in a wide variety of soil conditions
- Where a Trials tire falls short in braking and loose soil conditions, the 525 Cheater bridges that gap to make it the Ultimate Hybrid off-road tire
- "It's almost like cheating" The 525 has an open tread pattern that shines in soft Loose and loamy terrain
- Adds confidence even in the most demanding terrain
- Now available in 16" size for the smaller bikes
- NHS (Not for Highway Service)

## SPEED RATING / INDICE DE VITESSE

Code	MPH	KM/H
M	81	130

Part No.	Size	Load Index	Speed Symbol	Rim Size	Diameter	Width	Ply Rating	Tube Type	Max Load	Maximum Air Pressure (PSI)
01-04338	90/100-16	51	M	2.15	23.07	3.54	4	T/T	195	33
01-04317	110/100-18	64	M	2.5	26.65	4.29	4	T/T	279	33
01-04320	120/100-18	68	M	2.75	27.44	4.69	4	T/T	315	33
01-04318	110/90-19	62	M	2.5	26.81	4.29	4	T/T	264	33
01-04319	120/90-19	66	M	2.75	27.48	4.69	4	T/T	300	33

TERMS &  
INDEX

NEW

HELMETS &  
GOGGLESFASHION &  
APPAREL

ACCESSORIES

ENGINE &  
EXHAUST

DRIVE

SUSPENSION

CONTROLS  
& CARBBRAKES &  
ROTORSTIRES &  
TUBESLIGHTING &  
ELECTRICALBATTERIES &  
CHARGERSOFF-SHORE  
BRANDSOIL FILTERS &  
CHEMICALS

TOOLS

TRAILER