

SHINKO TIRES / PNEUS SHINKO

SHINKO
MOTORCYCLE TIRES



003 STEALTH RADIAL

CODE B | KEYWORD 9

- Slick/dimple design, great for production and drag racing, and serious sport riding
- Soft compound for rapid warm-up, gives racing slick like performance
- W speed rated (168 mph), Aramid belted, DOT approved
- Available in Ultra-Soft compound- great for drag racing and track use

Front / Avant

Rear / Arrière



SPEED RATING / INDICE DE VITESSE

Code	MPH	KM/H
W	168	270
J	62	100

DOT

Part No.	Size	Load Index	Speed Symbol	Rim Size	Diameter	Width	Ply Rating	Tube Type	Max Load	Maximum Air Pressure (PSI)
Front										
01-04001	120/60ZR17	55	W	3.5	22.68	4.8	R	T/L	218	42
01-04002	120/70ZR17	58	W	3.5	23.62	4.8	R	T/L	236	42
01-04008	120/70ZR17 U-SOFT	58	W	3.5	23.62	4.8	R	T/L	236	42
01-04433	120/60ZR17 U-SOFT	55	W	3.5	22.68	4.8	R	T/L	218	42
Rear										
01-04003	160/60ZR17	69	W	4.5	24.57	6.34	R	T/L	325	42
01-04004	170/60ZR17	72	W	4.5	25.04	6.61	R	T/L	355	42
01-04005	180/55ZR17	73	W	5.5	24.8	7.01	R	T/L	365	42
01-04009	180/55ZR17 U-SOFT	73	W	5.5	24.8	7.01	R	T/L	365	42
01-04006	190/50ZR17	73	W	6	24.49	7.48	R	T/L	365	42
01-04010	190/50ZR17 U-SOFT	73	W	6	24.49	7.48	R	T/L	365	42
01-04007	200/50ZR17	75	W	6.25	24.88	7.87	R	T/L	387	42
01-04155	180/55ZR18	75	W	6.25	24.88	7.87	R	T/L	387	42
01-04437	200/50ZR17 U-SOFT	74	W	5.5	25.79	7.01	R	T/L	375	42

SMALL BORE TIRES

Part No.	Size	Load Index	Speed Rating	Diameter	Width	DOT	Ply Rating	Tube Type	Max Load
Front									
01-04431	100/90-12 Soft	49	J	—	—	Y	—	TL	—
01-04432	100/90-12 Medium	49	J	—	—	Y	—	TL	—
Rear									
01-04434	120/80-12 Medium	55	J	—	—	Y	—	TL	—
01-04435	120/80-12 Hard	55	J	—	—	Y	—	TL	—

010 APEX RADIAL

- Tread designed for serious sport riding
- Rear tires feature Zero Degree JLSB (Joint-Less Steel Belted) state-of-the-art technology for added stability and strength
- Front tires are Aramid belted for enhanced high speed performance
- Intermediate compound, tread radius designed for enhanced high speed cornering
- "W" speed rated (168 mph), DOT approved

Front / Avant

Rear / Arrière



SPEED RATING / INDICE DE VITESSE

Code	MPH	KM/H
W	168	270

DOT

Part No.	Size	Load Index	Speed Symbol	Rim Size	Diameter	Width	Ply Rating	Tube Type	Max Load	Maximum Air Pressure (PSI)
Front										
01-04036	120/60ZR17	55	W	3.5	22.68	4.8	R	T/L	218	42
01-04037	120/70ZR17	58	W	3.5	23.62	4.8	R	T/L	236	42
Rear										
01-04038	150/60ZR17 JLSB	66	W	4.25	24.09	5.94	R	T/L	300	42
01-04039	160/60ZR17 JLSB	69	W	4.5	24.57	6.34	R	T/L	325	42
01-04041	180/55ZR17 JLSB	73	W	5.5	24.8	7.01	R	T/L	365	42
01-04042	190/50ZR17 JLSB	73	W	6	24.49	7.48	R	T/L	365	42
01-04043	190/55ZR17 JLSB	75	W	6	25.28	7.48	R	T/L	387	42

