

TRANSOIL EXPERT 10W-40

**Lubricant for gearboxes with wet clutch
Technosynthese® - Ester**

TYPE OF USE

Specially formulated for gearboxes with wet clutch using different oil from the engine oil: gearbox case separated from engine crankcase.

Gearboxes operating in severe conditions: racing, competition, high temperature, high load...

All type of Motorbikes: Road, Trails, Cross (2 or 4 Stroke engine), Enduro (2 or 4 Stroke engine), Mopeds, Scooters, Quads, ATV, UTV... etc.

Suitable when manufacturers require for the transmission an SAE 10W-40 engine oil or SAE 90 gearbox oil.

PERFORMANCES

STANDARDS API GL-4

Synthetic lubricant Technosynthese® - Ester reinforced with synthetic base stocks.

Very easy gear shifting.

Very high resistance in extreme conditions (pressure, temperature) thanks to its high viscosity at high temperature: viscosity grade SAE 40.

Specific additivation for gear protection.

Avoid clutch slippage for better transmission efficiency.

Dispersant properties to maintain clutch discs clean.

Extreme Pressure, Anti-wear, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
-----------------	-----------	--------

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



TRANSOIL EXPERT 10W-40

Lubricant for gearboxes with wet clutch
Technosynthese® - Ester

Density at 20°C (68°F)	ASTM D1298	0.869
Viscosity at 40°C (104°F)	ASTM D445	100.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	15.4 mm ² /s
Viscosity Index	ASTM D2270	163.0
Pour point	ASTM D97	-36.0 °C / -33.0 °F
Flash point	ASTM D92	240.0 °C / 464.0 °F