

**FORK OIL EXP M/H 15W**

**Hydraulic Fluids for any type of telescopic forks  
Technosynthese®**

**TYPE OF USE**

Specially designed for any type of fork, upside-down ("USD") forks or conventional ("right-side-up») forks.

**PERFORMANCES**

Specific Technosynthese® formulation that contains exclusive anti-friction additive specially developed by MOTUL to create easier sliding and to avoid drag in the fork.

Stable absorption trough extended range of temperature thanks to the use of synthetic base stocks.

Seals protection: excellent lubricant / elastomer compatibility.

Anti-wear, anti-corrosion, anti-foaming.

**RECOMMENDATIONS**

MOTUL Fork Oil Expert can be mixed to obtain the required absorption effect. Use the exact quantity recommended by the fork manufacturer.

**PROPERTIES**

Density at 20°C (68°F)	ASTM D1298	0.865
Viscosity at 40°C (104°F)	ASTM D445	58.1 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	8.4 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	116.0
Flash point	ASTM D92	232.0 °C / 449.0 °F
Pour point	ASTM D97	-33.0 °C / -27.0 °F