

**FORK OIL FACTORY LINE 2.5W**

**High Performance Hydraulic Fluid for any telescopic fork**  
**100% Synthetic**  
**Very Light**

**TYPE OF USE**

Hydraulic fluid for racing applications.  
Specially formulated for SHOWA, KAYABA, OHLINS, WP forks, and any type of upside/down or conventional telescopic fork.

**PERFORMANCES**

Reduced internal friction, specially fork tubes and seals thanks to the exclusive anti-friction additive designed and developed by MOTUL.  
Outstanding suspension performance as soon as riding and maintained performance in time.  
High performance anti-foam avoiding air transfer to the air chamber to maintain suspension performance.  
Anti-wear and extreme pressure properties. Anti-corrosion. Seals protection.

**RECOMMENDATIONS**

MOTUL Fork Oil Factory Line can be mixed to obtain the required absorption effect.  
Use the exact quantity recommended by the fork manufacturer.

**PROPERTIES**

Viscosity grade		2.5W
Density at 20°C (68°F)	ASTM D1298	0.834
Viscosity at 40°C (104°F)	ASTM D445	15.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	3.5 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	112.0
Pour point	ASTM D97	-39.0 °C / -38.0 °F
Flash point	ASTM D92	205.0 °C / 401.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com